

Torque Specifications (Cont'd)

Steering linkage (4WD)	Part tightened	N·m	kgf·cm	ft·lbf
		Pitman arm x Sector shaft	177	1,800
	Pitman arm x Relay rod	90	920	67
	Tie rod tube clamp bolt	25	260	19
	Tie rod x Relay rod	90	920	67
	Tie rod x Knuckle arm	90	920	67
	Relay rod x Idler arm	59	600	43
	Relay rod x Steering damper	59	600	43
	Knuckle arm x Steering knuckle	183	1,870	135
	Idler arm x Idler arm bracket	78	800	58
	Idler arm bracket x Frame	142	1,450	105

BODY

Torque Specifications

Part tightened	N·m	kgf·cm	ft·lbf
MOON ROOF			
Removable roof hinge case x Body	3.4	35	30 in·lbf
Removable roof lock base x Body	5.9	60	52 in·lbf
Removable roof hinge x Removable roof	2.9	30	26 in·lbf
Removable roof handle x Removable roof	2.9	30	26 in·lbf
ONE-TOUCH TAIL GATE			
Tail gate stay x Tail gate	14	140	10
SEAT			
Front Seat			
Seat adjuster x Body	37	375	27
Rear Jump Seat (Extra Cab)			
Back panel trim x Body	4.9	50	43 in·lbf
Seat cushion x Body	4.9	50	43 in·lbf
SEAT BELT			
Seat belt anchor x Body	43	440	32
Seat belt guide x Body	43	440	32
Buckle x Body	43	440	32